




<b>TYRES</b>	700 X 40c brand Kenda, K198
<b>RIM</b>	black aluminum, double wall rims
<b>BRAKES</b>	mechanical Disc Brake System, brand Logan, model LB-DX2016, lever with cut off sensor
<b>SHIFTER</b>	Shimano Tourney 7 speed with rear derailleur
<b>FRONT FORK</b>	Zoom 106D, Suspension fork - spring system
<b>CRANKSET</b>	Prowheel 38T - 170mm, chain KMC
<b>PEDALS</b>	Neco-WP-302, city
<b>FRAME</b>	aluminum 6061, with rear wheel lock
<b>MAX SPEED</b>	25Km/h
<b>SEAT</b>	CY - Argento logo, high elastic foam, black
<b>SEAT POST</b>	Aluminum seat post with internal shock absorber
<b>HANDLEBAR</b>	aluminum, Zoom mtb
<b>GRIPS</b>	XL - Argento logo, ergonomic - rubber
<b>LIGHTS</b>	front light: LED, DH003E 36V DC. Rear light: LED, DR009 (rear carrier)
<b>DISPLAY</b>	LCD display waterproof with battery level indicator - PAS level indicator - On / Off light - Walk assist - Error codes - Bluetooth connection - Parameter configuration menu
<b>MOTOR</b>	Bafang 36V 250W 45Nm, rear
<b>FENDER</b>	in PVC with side supports - black/black
<b>KICKSTAND</b>	rear, side model, adjustable
<b>REAR RACK</b>	rear (max load 25 kg)
<b>MAX LOAD WEIGHT</b>	100kg
<b>BATTERY</b>	36V 10.4Ah 374Wh, integrated
<b>RECHARGE PACK BATTERY</b>	42.0V 2.0A
<b>RANGE*</b>	from 40 to 70km, this data depends on: level of assistance used, driver's weight, muscle power applied in pedaling, tire pressure, road slope, number of stops and restarts
<b>GROSS WEIGHT BATTERY</b>	2.6Kg
<b>NET WEIGHT</b>	22.9Kg
<b>GROSS WEIGHT</b>	~25.5Kg
<b>PACKAGING DIMENSIONS</b>	148 x 25 x 84cm

E-bike dimensions



28" tyres



Installed rear rack



LCD display



AR-BI-220011 | 8052679456062



Imported and distributed by M.T. Distribution S.r.l.  
Società unipersonale soggetta a direzione e coordinamento di Electron S.p.A.  
via Bargellino 10, 40012, Calderara di Reno, (BO) Italy  
P.I. 04177060375 | C.F. 0119840377 | REA BO-236546 | Capitale Sociale 10.000,00 iv.  
www.platum.com

\* Subject to variations based on the rider's weight, on the road conditions and on the temperature.

All images are inserted for illustrative purposes, the products may undergo changes.