













Two brake controls and high-performance bell

The way you move

URBAN LIGHTWEIGHT

FRAME	steel
SUSPENSIONS	no a la l
SPEED*	L1: <= 6km/h L2:<= 20km/h L3: <= 25km/h (max speed)*
MAXIMUM SLOPE*	15%
BRAKES	front drum brake and electronic rear brake, two brake controls
TYRES	10" inner tube
MAXIMUM LOAD	100kg
RIDER	check the current legislation in your country
OPERATING TEMPERATURE	-5 °C / 45 °C
PROTECTION LEVEL	IPX5
CHARGING TIME	approax 4 hours
RANGE**	up to 25km
MOTOR	350W brushless, 17.7Nm
PEAK POWER	600W
DISPLAY	integrated LED
BATTERY	36V 7.5Ah 270Wh
LOW VOLTAGE PROTECTION	31V ± 0.5V
CURRENT LIMIT	17A ±1A
KERS	yes
LIGHTS	front and rear LED
WIRELESS CONNECTION	yes
APP	yes
TURN SIGNALS	yes
NET WEIGHT	15.4kg
GROSS WEIGHT	18.5kg
OPEN ITEM DIMENSIONS	1170 x 470 x 1180mm
CLOSED ITEM DIMENSIONS	1170 x 470 x 485mm
PACKAGING DIMENSION	1210 x 215 x 510 mm

^{*} Always respect the highway code and the regulations in force in the country where the electric scooter is used.

Only 15.4kg of weight, easy to carry







10" inner tube tyres



350W motor, Peak Power 600W





AR-MO-220004 | 8056711539836



 $[\]ensuremath{^{**}}$ Subject to variations based on the rider's weight, on the road conditions and on the temperature.