

Urban e-Mobility





The way you move **Urban** Beat





Magnesium frame

Foldable frame

Technical specifications

Basic info	
Tyres	20 "X 2.125
Rims	magnesium alloy, 6-spoke
Brakes	front and rear mechanical disc brake
Gear	SHIMANO Tourney 6 speed
Fork	hard fork, magnesium alloy
Crankset	44T steel chainrig - 165mm
Pedals	foldable
Frame	magnesium alloy, foldable
Max speed*	25 km/h
Saddle	ergonomic pvc
Seat post	aluminum alloy
Handlebar	aluminum alloy
Grips	ergonomic rubber
Fender	pvc, black
Kickstand	rear, side model
Carrrier	not included
Max load	100kg

LCD display

Product Sku: DU-BI-210003

Ean Code: **8052679453061**

Electric system	
Lights	front and rear LED light
Display	LCD waterproof, Power On/Off, Battery capacity indicator, PAS level mode, Speed informations (Current, Maximum), Distance and Duration informations (ODO, TRIP, Time), Front Light On/Off, Error Codes
Motor	36V, 250W, 45Nm, rear
Battery	36V, 10.5Ah, 378Wh integrated into the frame
Charger	input: 100-240V, 2.5A / output: 42V, 2.0A
Charging time	4/6 hours
Range**	from 40 to 70 km, this figure depends on: level of assistance used, weight of the cyclist, muscle power applied when pedaling, tire pressure, road slope, number of stops and restarts

Dimensions and Weights		
Battery weight	2.0kg	
Weight w/o battery	18.5kg	
Weight tot.	20.5kg	
E-bike dimensions	1520 x 580 x 1070mm - folded 830 x 500 x 720mm	
Pack dimensions	830 x 420 x 675mm	

* Always respect the highway code and the regulations in force in the country of use. ** Subject to variations based on driver weight, road conditions and temperature.