



The way you move

COMFORTABLE RIDE

FRAME	aluminum alloy
SUSPENSIONS	no
SPEED*	L1: < 6km/h; L2: < 15km/h; L3: < 20km/h; L4: < 25km/h (max speed)
MAXIMUM SLOPE*	15%
BRAKES	front drum brake, rear electronic and drum brke, double brake lever
TYRES	front 12" and rear 10", inner tube
MAXIMUM LOAD	120kg
RIDER	check the current legislation in your country
OPERATING TEMPERATURE	-0 °C / 45 °C
PROTECTION LEVEL	IPX5
CHARGING TIME	approax 5 hours
RANGE**	up to 30km
MOTOR	350W brushless, 17Nm
PEAK POWER	500W
DISPLAY	integrated colour LED with smartphone holder
BATTERY	36V 12.5Ah 450Wh
LOW VOLTAGE PROTECTION	31V ± 0.5V
CURRENT LIMIT	18A ±1A
KERS	yes
LIGHTS	front and rear LED
WIRELESS CONNECTION	yes
APP	yes
TURN SIGNALS	yes
NET WEIGHT	18.2kg
GROSS WEIGHT	23.7kg
OPEN ITEM DIMENSIONS	1230 x 685 x 1285mm
CLOSED ITEM DIMENSIONS	1230 x 685 x 570mm
PACKAGING DIMENSION	1245 x 200 x 600 mm

12" front and 10" rear tyres

ARGENT



Load up to 120kg

Up to 30km of range, 450Wh battery



350W motor, Peak Power: 500W







* Always respect the highway code and the regulations in force in the country where the electric scooter is used. $\ast\ast$ Subject to variations based on the rider's weight, on the road conditions and on the temperature.



